

TAILORED TOOLBOXES FORM DOUBLE DOOR WITH CENTRAL UPRIGHT

| Customer data Company Name | | Δddres | 35 | | n |
|---|--------------------------------|-------------------------------------|--------------------------|---|---|
| | Address n n Prov Country | | | | |
| | Tax Code | | | | |
| Phone | | | | | |
| nese data will be processed in compliance | | | | | |
| e request a quote for this | | | | | , -,- |
| DOUBLE DOOR WITH CEN | NTRAL UPRIGHT: | MATERIAL: | | THICKNESS: | HANDLES: |
| | | ☐ Galvanized (thickness max | | 1 8/10 2 | ☐ M100061 n |
| | H | ☐ Stainless S | Steel (8*) | 10/10 6 | ☐ M10017 n |
| | | ☐ Flowered Stainless S | 60 7 Steel | 12/10 30 | ☐ M10018 n |
| | P | ☐ Stainless Stee Bright Anneale | | 15/10 60 | ☐ R18110 n |
| | QUANTITY: | (thickness 15/ | | 20/10 2 (only stainless steel) | |
| | MEASURES: | | | ☐ TOOLBOX | воттом 90° |
| | L | mm. | | R: \square in the middle | |
| | Н | mm. | DIVIDER | to measure mm. | |
| central | Р | | | 1- | |
| %) Customer preferences. Two doors opening, Pinned sheet metal, Pinned hinges, Toolb | | | | in the middle to measure (from the top) | e mm. |
| Key Lock Steel Key Lock Key | Stainless Steel Key Lock "Frig | el Key Lock Gal o" for Shutter L | C70505M | Closing Hood 65000 M Shelf | |
| R72110 T75105 | | | | | |
| R72110 T75105 TOOLBOXES SUPPORTS Pair of Galvanized Brackets Brackets With | vanized Pair of Galv | ets Black Br | rackets Galva | air of Universal anized Brackets St | Pair of Universal ainless Steel Brackets |
| TOOLBOXES SUPPORTS Pair of Galvanized Pair of Galvanized Brackets Brackets with | vanized Pair of Galv | ets Black Br | niversal Parackets Galva | | |

OAII rights reserved, exclusive property of Truck S.r.I. Any use, total or partial, (photos and content included in this form) is prohibited